



— DES-1005D

5-Port 10/100Mbps Switch for SOHO

The DES-1005D is an unmanaged 10/100Mbps switch designed to enhance small workgroup performance while providing a high level of flexibility. Powerful yet easy to use, this device allows users to simply plug any port to either a 10Mbps or 100Mbps network to multiply bandwidths, boost response time and satisfy heavy load demands.

5 Auto-sensing 10/100Mbps Ports

The switch comes with 5 10/100Mbps ports, allowing a small workgroup to flexibly connect to Ethernet and Fast Ethernet and integrate. These intelligent ports detect the network speed and auto-negotiate between 10BASE-TX and 10BASE-T, as well as between full- and half-duplex.

Flow Control for Secure Transmission

All ports support 802.3x flow control. This function minimizes dropped packets by sending out collision signals when the port's receiving buffer is full. Flow control is available in the full-duplex mode.

Auto-negotiation of MDI/MDIX Cross Over

All ports support auto-negotiation of MDI/MDIX cross over. This eliminates the need for cross over cables or uplink ports. Any port can simply plug to a server, a hub or a switch, using the usual straight-through twisted-pair cable.

SOHO Plug-and-Play

With 5 plug-and-play ports, the switch is a perfect choice for the small workgroup to upgrade performance in a client/server environment. The ports can be connected to servers in full-duplex, or hubs in half-duplex.

Desktop Power

With low-cost connection per-port, the switch can also be set up for direct connection from the PCs. This relieves data bottleneck by giving each workstation a dedicated bandwidth on the network.

Features

- 5 10/100Mbps ports
- Per-port auto MDI/MDIX
- All ports support full/half-duplex, network speed auto-negotiation
- Per-port 802.3x flow control for protection against data loss
- Auto-learning of network configuration
- Secure store-and-forward switching scheme
- Auto-correction of reverse twisted-pair polarity
- Compact palm-sized

DES-1005D

Technical Specifications

10/100Mbps Unmanaged Switch

General

Standards

- IEEE 802.3 10BASE-T Ethernet
- IEEE 802.3u 100BASE-TX Fast Ethernet
- ANSI/IEEE 802.3 NWay auto-negotiation
- IEEE 802.3x Flow Control

Protocol

CSMA/CD

Data Transfer Rates

- Ethernet:
 - 10Mbps (half-duplex)
 - 20Mbps (full-duplex)-
- Fast Ethernet:
 - 100Mbps (half-duplex)
 - 200Mbps (full-duplex)

Topology

Star

Network Cables

- 10BASE-T:
 - 2-pair UTP Cat. 3 (100 m)
 - 4-pair UTP Cat. 4, 5 (100 m)
 - EIA/TIA-568 150-ohm screened twisted-pair (STP) (100 m)
- 100BASE-TX:
 - 4-pair UTP Cat. 5 (100 m)
 - EIA/TIA-568B 150-ohm screened twisted-pair (STP) (100 m)

Number of Ports

10/100Mbps port x 5 with auto MDI/MDIX

Twisted-pair Rx Reverse Polarity

Auto-correction

LED Report

Per device:

- Power

Per port:

100Mbps Link/Activity, 10Mbps Link/Activity

Performance

Transmission Method

Store-and-forward

Switch Capability

1Gbps

Filtering Address Table

2K entries per device

MAC Address Learning

Automatic update

Buffer Memory

64KBytes per device

Packet Filtering Rates

- 10BASE-T: 14,880 pps per port (half-duplex)
- 100BASE-TX: 148,800 pps per port (half-duplex)

Packet Forwarding Rates

- 10BASE-T: 14,880 pps per port (half-duplex)
- 100BASE-TX: 148,800 pps per port (half-duplex)

Physical & Environmental

Power Input

- AC 9V/1A
- DC 7.5V/1A
- Switching 5V/1.2A

* Different Switch versions are packed with different power types

Power Consumption

2.83 watts

Operating Temperature

0°~50°C (32°~122°F)

Storage Temperature

-10°~70°C (14°~158°F)

Operating Humidity

10%~90%

Storage Humidity

5%~90%

Dimensions (W x D x H)

142 x 115 x 31 mm (5.6 x 4.5 x 1.2 inches)

Emission (EMI)

- FCC Class B
- ICES-003 Class B
- CE Class B
- C-Tick Class B
- VCCI Class B

Safety

CSA International

MTBF

99,663 hours



D-Link Worldwide Offices

U.S.A	TEL: 1-800-326-1688	FAX: 1-866-743-4905	Singapore	TEL: 65-6774-6233	FAX: 65-6774-63225
Canada	TEL: 1-905-8295033	FAX: 1-905-8295223	Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
Europe, UK & Ireland	TEL: 44-20-8955-9000	FAX: 44-20-8955-9002	India	TEL: 91-22-2652 6696	FAX: 91-22-2652 8914
Germany	TEL: 49-6196-77990	FAX: 49-6196-7799300	Middle East (Dubai)	TEL: 971-4-391-6480	FAX: 971-4-390-8881
France	TEL: 33 1 30 23 86 88	FAX: 33 1 30 23 86 89	Egypt	TEL: 202-291-9035	FAX: 202-291-9051
Netherlands	TEL: 31-10-282-1445	FAX: 31-10-282-1331	Turkey	TEL: 90-212-289-5659	FAX: 90-212-289-7606
Belgium & Luxemburg	TEL: 32(0)2 517 7111	FAX: 32(0)2 517 6500	Iran	TEL: 90-212-289-5659	FAX: 90-212-289-7606
Switzerland	TEL: 41 (0) 1 832 11 00	FAX: 41 (0) 1 832 11 01	Pakistan	TEL: 92-21-454-8158	FAX: 92-21-453-5103
Sweden	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901	Israel	TEL: 972-9-9715700	FAX: 972-9-9715601
Denmark	TEL: 45-43-969040	FAX: 45-43-424347	Latin America	TEL: 56-2-5838-950	FAX: 56-2-5838953
Norway	TEL: 47 99 300 100	FAX: 47 22 30 95 80	Brazil	TEL: 55-11-2185-9300	FAX: 55-11-2185-9322
Finland	TEL: 358-10 309 8840	FAX: 358-10 309 8841	South Africa	TEL: 27-12-665-2165	FAX: 27-12-665-2186
Italy	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723	Russia	TEL: 7-495-744-0099	FAX: 7-495-744-0099
Spain	TEL: 34 93 409 0770	FAX: 34 93 491 0795	Japan	TEL: 81-3-5781-0963	FAX: 81-3-5781-0965
Portugal	TEL: 351 21 8688493	FAX: 30 210 9916902	Korea	TEL: 82-2-890-5491	FAX: 82-2-890-549
Greece	TEL: 30 210 9914 512	FAX: 36 (0) 1 461 30 09	China	TEL: 86-10-58635800	FAX: 86-10-58635799
Czech Republic	TEL: 420 224 247 500	FAX: 48 (0) 22 583 92 7	Taiwan	TEL: 886-2-6600-0123	FAX: 886-2-6600-3939
Hungary	TEL: 36 (0) 1 461 30 00	FAX: 48 (0) 22 583 92 7	Headquarters	TEL: 886-2-6600-0123	FAX: 886-2-6600-9898
Poland	TEL: 48 (0) 22 583 92 7				